

Artistically Abstracted

Style	8530
Construction	High Performance Luxury Vinyl Tile
Wear Layer	20 mil (0.5 mm)
Finish	Ironclad Anti-Scratch Ceramic PU Finish (Anti-Bacterial)
Overall Thickness	0.197" (5 mm)
Reference Specification	Class III Printed Film Vinyl Tile, Type B (embossed)

Installation

Installation Type	Glue Down
Adhesive	AtlasMasland Premium Spray Adhesive or Modular Tile/LVT Adhesive

Packaging

Tile Size	18" x 36" (45.72cm x 91.44cm)	Coverage/Piece	4.48 sf
Pieces per box	6	Coverage/Carton	26.9 sf (2.50 m ²)
Square feet per box	26.9 (2.50 m ²)	Coverage/Pallet	36 boxes / 968.4 sf (90 m ²)
Weight per box	41.89lbs (19.00kg)		

Testing

Test	Standard	Minimum Requirement	Results
Critical Radiant Flux	ASTM E648	≥0.45 Watts/cm ² (Class 1)	Passes
Smoke Density	ASTM E662	≤450	Passes
Slip Resistance	ASTM D2047	ADA Compliant	≥0.6 (Dry)
Dimensional Stability	ASTM F2199	0.02" lin. ft. max	Passes
Flexibility	ASTM F137	≤1.0" (no cracks or breaks)	Passes
Residual Indentation	ASTM F1914	Avg. < 8%	Passes
Static Load	ASTM F970	250 psi min	Passes
Chemical Resistance	ASTM F925	No more than slight change	Passes
Resistance to Heat	ASTM F1514	ΔE < 8 avg. max	Passes
Resistance to Light	ASTM F1515	ΔE < 8 avg. max	Passes
Thickness Tolerance	ASTM F386	±0.005"	Passes
Indoor Air Quality	CHPS 01350 LEED EQ 4.3	Low VOC	FloorScore Certified

Warranty

10 year – Limited Commercial Wear Warranty 15 year – Light Commercial Wear Warranty

See warranty documentation for full details of terms and conditions.



Order Samples at 1-888-633-4770 or atlasmasland.com | AtlasMasland | 716 Bill Myles Drive | Saraland, AL 36571